



REED SWITCH

MKA-07101MS

Reed relays, Security, Limit switching, Telecoms, Office equipment (up to 10kHz)

Switching Carry current, A	0,1 0,3	Switching power, W, VA	10
Switching voltage, V	100	Pull-in range, AT	10...40

Any DC combination of V&A not to exceed the Switching power.



Electrical Data

Pull-in range, AT	10...40
Release range, AT, min	4
Resetting Ratio	0,35...0,95
Breakdown voltage, V, not less	
AC/DC	110/150
Contact resistance, Ω	0,2
Operating time including bounce, ms	0,3
Release time including bounce, ms	0,1
Capacitance, pF, not more	0,4
Insulations resistance, G Ω , not less	1
Operation frequency, Hz	100
Switching current frequency, kHz, not more	10
Life expectancy, switching cycles x10 ⁶	(1...50)


Environmental Data

Contact type	A
Vibration (1...500 Hz), g, not more	10
Resonant frequency, Hz	12000
Shock (1±0,3) ms, g, not more	150
Weight, g, not more	0,08
Contact material	Ru
Operating temperature, °C	-60...125
Humidity, %, not more	98


Order information

Delivery of reed switches with formed and/or cropped leads and with narrow pull in ranges is available by agreements.

Certifications



Test coil



RYAZAN METAL CERAMICS INSTRUMENTATION PLANT, JSC

51V, NovayaSt.,390027,Ryazan, Russia www.rmcp.com
Sales: phone +7 (4912) 240-234, fax +7(4912) 240-234 oves@rmcip.ru